

FM400 Hand Length

110# Performance Filament Tape

DESCRIPTION

An economical fiberglass reinforced polypropylene film combined with an aggressive 'solventless' pressure-sensitive adhesive provides excellent adhesion to corrugated cartons and outstanding holding power.

PRODUCT APPLICATION

Designed for the majority of packaging, palletizing and unitizing applications.

tufflexpackaging.com

1 844-VERITIV

1000 Abernathy Rd. NE, Bldg. 400,
Suite 1700, Atlanta, GA 30328, USA

© 2019 Veritiv Corporation. All rights reserved. TUFFflex is a trademark of Veritiv Corporation or its affiliates. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard terms and conditions of sale apply exclusively to all orders and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications. WF237768

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

BACKING	1.0 mil (25µ) Biaxial Oriented PP Film
ADHESIVE	Synthetic Rubber/Resin
TENSILE STRENGTH (lb/in of width) PSTC-131	110 (482 N/25mm)
ELONGATION (% at break) PSTC-131	3.5
ADHESION TO STEEL (oz/in of width) (at 90° peel angle) PSTC-101	63 (17.2 N/25mm)
TOTAL THICKNESS PSTC-131	4.0 (0.102mm)
QUICK STICK (oz/in of width)	To Kraft 8 (2.2 N/25mm) To Steel 30 (8.2 N/25mm)
SHEAR TO KRAFT PAPER (hours) (1" x 1" x 1000 grams)	>96
COLOUR	Clear