

FB720 Hand Length

Premium Flatback Tape

DESCRIPTION

A moisture resistant kraft flatback paper tape with an aggressive, pressure-sensitive natural/synthetic rubber adhesive. Designed to offer a positive, attractive seal and excellent adhesion to minimize carton sealing failures and prevent pilferage. Considered by many as the "industry standard." Excellent balance of machine and cross direction tensile and tear strength. Remains strong under moist conditions. Product is not repulpable.

PRODUCT APPLICATION

Carton sealing, packaging, silk screening, picture framing, beaming/leasing, splicing, and tabbing.

GOVERNMENT COMPLIANCE

Approved as packaging tape by both US Postal Service and UPS (United Parcel Service)
PPP-T-42C, Type II
C.I.D. A-A-883B, Type II

TUFFflex™

tuffflexpackaging.com

1 844-VERITIV

1000 Abernathy Rd. NE, Bldg. 400,
Suite 1700, Atlanta, GA 30328, USA

© 2020 Veritiv Corporation. All rights reserved. TUFFflex is a trademark of Veritiv Corporation or its affiliates. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard terms and conditions of sale apply exclusively to all orders and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications. WF350844

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. This data should not be considered specification.

BACKING	Kraft Flatback
ADHESIVE	Natural/Synthetic Rubber
TENSILE STRENGTH (lb/in of width) PSTC-131	42 (184 N/25mm)
ELONGATION (% at break) ASTM D3759	7
ADHESION TO STEEL (oz/in of width) PSTC-101	60 (16.4 N/25mm)
TOTAL THICKNESS PSTC-133	7.5 (0.19mm)
OPERATING TEMPERATURE RANGE	Application +50°F to +120°F (+10°C ~ +49°C) Operating -32°F to 200°F (-0°C ~ +93°C)
COLOUR	Brown