

# MK600 Hand Length

## Performance Paper Masking Tape

### DESCRIPTION

A beige, semi-bleached crepe paper coated with a pressure-sensitive natural/synthetic rubber adhesive. Conformable and flexible. A porch industry leader.

### PRODUCT APPLICATION

Designed primarily for general purpose bundling, protecting, and various industrial applications, interior paint masking, silk screening, mail rooms, golf club shaft (build-up), carpet pad/pad splicing, freezer tape and for light bundling, packaging, splicing and tabbing.

### GOVERNMENT COMPLIANCE

ASTM D6123/6123M, Type I  
C.I.D. A-A-883B, Type I

# TUFFflex™

[tufflexpackaging.com](http://tufflexpackaging.com)

1 844-VERITIV

1000 Abernathy Rd. NE, Bldg. 400,  
Suite 1700, Atlanta, GA 30328, USA

© 2020 Veritiv Corporation. All rights reserved. TUFFflex is a trademark of Veritiv Corporation or its affiliates. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard terms and conditions of sale apply exclusively to all orders and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications. WF350844

### NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

<b>BACKING</b>	Crepe Paper
<b>ADHESIVE</b>	Natural/Synthetic Rubber
<b>TENSILE STRENGTH</b> (lb/in of width) PSTC-131	23 (100.7 N/25mm)
<b>ELONGATION</b> (% at break) PSTC-131	7
<b>ADHESION TO STEEL</b> (oz/in of width) PSTC-101	40 (10.9 N/25mm)
<b>TOTAL THICKNESS</b> PSTC-131	5.5 (0.14mm)
<b>QUICK STICK TO STEEL</b> (oz/in of width) PSTC-5	18 (4.9 N/25mm)
<b>OPERATING TEMPERATURE RESISTANCE</b>	+50°F to +180°F (+10°C ~ +82°C)
<b>COLOUR</b>	Beige