

V02377

TUFFlex Ultra Película Manual

9 Micrones / 35 Calibre / 0.35 Mil

No deben considerarse como especificaciones limitantes

CARACTERISTICAS

VALORES

Proceso de fabricación	Fundido
Espesor (nominal)	9 Micrones / 35 Calibre/ 0.35 Mil
Color	Transparente
Ancho de Película (pulgadas)	18"
Largo (pies)	1500'
Peso Neto/Rollo (lbs-nominal)	3.78 lbs
Diámetro de Rollo (D.E, pulgadas)	6"
Tubo D.I.	3"

PRUEBAS

METODOS

VALORES

Opacidad	ASTM D1003	2%
Brillo	ASTM D2457	80%
Resistencia a la Tensión a la Rotura (DM)	ASTM D882	9000 psi
Resistencia a la Tensión a la Rotura (DT)	ASTM D882	3500 psi
Estiramiento a la Rotura (DM)	ASTM D882	135%
Estiramiento a la Rotura (DT)	ASTM D882	725%
Resistencia al desgarre Elmendorf (DM)	ASTM D1922	120 g
Resistencia al desgarre Elmendorf (DT)	ASTM D1922	140 g
Adherencia	ASTM D5458	75 g



tufflexpackaging.com

844-VERITIV

1000 Abernathy Rd NE | Building 400 | Suite 1700 | Atlanta, GA 30328 | USA

© 2017 Veritiv Corporation. Todos los derechos reservados. TUFFflex es una marca registrada de Veritiv Corporation o de sus afiliados.

V02377

TUFFlex Ultra Handwrap

9 Micron / 35 Gauge / 0.35 Mil

Not intended as limiting specifications

CHARACTERISTICS

CHARACTERISTICS	VALUES
Manufacturing Process	Cast
Thickness (nominal)	9 Micron / 35 Gauge / 0.35 Mil
Color	Clear
Film Width (inches)	18"
Length (feet)	1500'
Net Weight/Roll (lbs–nominal)	3.78 lbs
Roll Diameter (O.D., inches)	6"
Core I.D.	3"

TESTS

TESTS	METHODS	VALUES
Haze	ASTM D1003	2%
Gloss	ASTM D2457	80%
Tensile Strength at Break (MD)	ASTM D882	9000 psi
Tensile Strength at Break (TD)	ASTM D882	3500 psi
Elongation at Break (MD)	ASTM D882	135%
Elongation at Break (TD)	ASTM D882	725%
Elemdorf Tear Strength (MD)	ASTM D1922	120 g
Elemdorf Tear Strength (TD)	ASTM D1922	140 g
Cling	ASTM D5458	75 g

tufflexpackaging.com

844-VERITIV

1000 Abernathy Rd NE | Building 400 | Suite 1700 | Atlanta, GA 30328 | USA

© 2017 Veritiv Corporation. All rights reserved. TUFFlex is a registered trademark of Veritiv Corporation or its affiliates.

Ref: 86500 April 2017 TFTDSV02377MX

TUFFlex™