

WA530 Natural Machine Length

Performance Reinforced WAT

DESCRIPTION

Natural kraft 3-way fiberglass reinforced water-activated carton sealing tape, manufactured with a starch based adhesive.

PRODUCT APPLICATION

Used for two strip sealing cartons top and bottom. Works well on recycled cartons and non-unitized loads. Recommended for use on light weight to average cartons up to 20 pounds.

TUFFflex™

tufflexpackaging.com

1 844-VERITIV

1000 Abernathy Rd. NE, Bldg. 400,
Suite 1700, Atlanta, GA 30328, USA

© 2020 Veritiv Corporation. All rights reserved. TUFFflex is a trademark of Veritiv Corporation or its affiliates. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard terms and conditions of sale apply exclusively to all orders and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications. WF350844

CONSTRUCTION PER 3,000 SQUARE FEET (metric)

TOP PLY	20 lb Natural Kraft Paper (virgin fibers)
BOTTOM PLY	23 lb Natural Kraft Paper (virgin fibers)
LAMINATING ADHESIVE	High Melt Index Polypropylene Based Blend
WATER-ACTIVATED ADHESIVE	Synthetically Modified Starch
MD REINFORCEMENT	(1-1-1-1) per 70mm 110 Fiberglass
CD REINFORCEMENT	(1-1-1) Polyester 1.10" spacing at 44° angle
TOTAL BASIS WEIGHT	68.5 lb

PHYSICAL PROPERTIES:

CALIPER (mil)	5.3
MD TENSILE (lb/in)	55
CD TENSILE (lb/in)	23

ADHESION (WATER AT RECOMMENDED 110°F/43°C)

FIPAGO	2/0	45
	2/1	63
	5/0	65
	15/0	81
MCLAURIN	83	