

WA550 Natural Machine Length

Performance WAT

DESCRIPTION

3-way fiberglass reinforced natural kraft carton sealing tape, manufactured with water-activated adhesive.

PRODUCT APPLICATION

Used for two strip sealing cartons top and bottom. Works well on recycled cartons, and non-unitized loads. Recommended for use on light weight to average cartons up to 20 pounds.

TUFFlex™

tufflexpackaging.com

1 844-VERITIV

1000 Abernathy Rd. NE, Bldg. 400,
Suite 1700, Atlanta, GA 30328, USA

© 2020 Veritiv Corporation. All rights reserved. TUFFlex is a trademark of Veritiv Corporation or its affiliates. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard terms and conditions of sale apply exclusively to all orders and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications. WF350844

CONSTRUCTION PER 3,000 SQUARE FEET (metric)

TOP PLY	20 lb Natural Kraft Paper (virgin fibers)
BOTTOM PLY	23 lb Natural Kraft Paper (virgin fibers)
LAMINATING ADHESIVE	13 lb High Melt Index Polypropylene Based Copolymer
REMOISTENABLE ADHESIVE	14 lb Chemically Grafted Starch Based Copolymer Adhesive, Designated as S3911
MD REINFORCEMENT	1.58 lb (1-1-1-1) 110 Fiberglass (per 70mm), 5/8" spacing
CD REINFORCEMENT	1.48 lb (1-1-1) Polyester 1.10" spacing, 44° angle
TOTAL BASIS WEIGHT	73.1 lb

PHYSICAL PROPERTIES:

CALIPER (mil)	5.5
MD TENSILE (lb/in)	66
CD TENSILE (lb/in)	26

ADHESION (WATER AT RECOMMENDED 110°F/43°C)

FIPAGO	2/0	49
	2/1	70
	5/0	75
	15/0	86
MCLAURIN	89	