

WA560 Natural Machine Length

Performance WAT

DESCRIPTION

Natural kraft carton sealing tape manufactured with standard water-activated adhesive.

PRODUCT APPLICATION

Recommended for inner carton sealing or for lightweight cartons that will be shipped in unitized loads or full pallets.

CONSTRUCTION PER 3,000 SQUARE FEET (metric)

TOP PLY	57 lb (93 g/m ²) Natural Kraft Paper
WATER-ACTIVATED ADHESIVE	15 lb (24 g/m ²) Waxy Maize Starch Based Adhesive Designated as #410
TOTAL BASIS WEIGHT	72 lb (117 g/m ²)

PHYSICAL PROPERTIES:

CALIPER (mil)	5.6
MD TENSILE (lb/in)	45
CD TENSILE (lb/in)	23

ADHESION (WATER AT RECOMMENDED 110°F/43°C)

FIPAGO	2/0	23
	2/1	42
	5/0	48
	15/0	82
MCLAURIN	34	

TUFFlex™

tufflexpackaging.com

1 844-VERITIV

1000 Abernathy Rd. NE, Bldg. 400,
Suite 1700, Atlanta, GA 30328, USA

© 2020 Veritiv Corporation. All rights reserved. TUFFlex is a trademark of Veritiv Corporation or its affiliates. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard terms and conditions of sale apply exclusively to all orders and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications. WF350844