

WA750 Natural Machine Length

Ultra Reinforced WAT

DESCRIPTION

3-way fiberglass reinforced, strippable natural kraft carton sealing tape manufactured with water-activated adhesive.

PRODUCT APPLICATION

Used for two-strip sealing cartons top and bottom. Works well on recycled cartons and non-unitized loads. Recommended using on average to heavyweight cartons up to 65 pounds.

tufflexpackaging.com

1 844-VERITIV

1000 Abernathy Rd. NE, Bldg. 400,
Suite 1700, Atlanta, GA 30328, USA

© 2019 Veritiv Corporation. All rights reserved. TUFFflex is a trademark of Veritiv Corporation or its affiliates. While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard terms and conditions of sale apply exclusively to all orders and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications. WF237768

CONSTRUCTION PER 3,000 SQUARE FEET (metric)

TOP PLY	25 lb Natural Kraft Paper (virgin fibers)
BOTTOM PLY	30 lb Natural Kraft Paper (virgin fibers)
LAMINATING ADHESIVE	15.5 lb High Melt Index Polypropylene Based Copolymer
REMOISTENABLE ADHESIVE	16 lb Chemically Grafted Starch Based Copolymer Adhesive, Designated as S3911
MD REINFORCEMENT	5.33 lb (1-1-1-1) 75 Fiberglass (per 3"), ½" spacing
CD REINFORCEMENT	2.91 lb (1-1-1), 150 Fiberglass, 0.55" spacing, 43° angle
TOTAL BASIS WEIGHT	94.7 lb

PHYSICAL PROPERTIES:

CALIPER (mil)	7.5
MD TENSILE (lb/in)	89
CD TENSILE (lb/in)	32

ADHESION (WATER AT RECOMMENDED 110°F/43°C)

FIPAGO	2/0	38
	2/1	58
	5/0	69
	15/0	87
MCLAURIN	86	